

NORTH LAKE TAHOE FIRE PROTECTION DISTRICT

866 Oriole Way – Incline Village, NV 89451-9439 (775) 831-0351 Fax (775) 831-2072 www.nltfpd.net

Mobile Food Truck Application

Applicant______Food Truck Name_____Contact Cell Phone

Contact Email	Billing Street Address_	Billing City/ZIP	
Scope of Work			
Times of Operation in In	cline Village/Crystal Bay		
Following the a	dopted Fire Code, a permit is required for n	nobile food preparation vehicles equipped with app	oliances
that produce smoke or g	rease laden vapors. If applicable, please acki	nowledge the following requirements:	
	Adopted Fire Code, Nevada State Fire Mar	shal, and NFPA requirements.	Initial
A permit is required from N with the Fire Inspector.	LTFPD prior to operating in Incline Village/Crysta	Bay. The permit can only be issued after a site inspection	
	ation, unobstructed, and securely anchored (Section	Class K extinguishers (Section 906.4). Extinguishers shall be 906.4). Extinguisher shall be currently serviced by	е
	duces grease laden vapors shall be provided with a shall be cleaned in accordance with Section 603.3	kitchen exhaust hood, in accordance with Section 607	
		omatic fire extinguishing system, following Section 906.4 ntly serviced by a licensed contractor with the State Fire	
Z21.69/CSA 6.16 . The conn	nector shall be installed in accordance with the manu	opining with an appliance connector complying with ANSI affacturer's specifications. Appliances shall be limited by s and appliance's manufacturer's specifications (Section	
	on the vehicle and fuel-gas piping <i>shall</i> be inspect with the USDOT to requalify LP-gas cylinders (Sect	ted annually by an approved inspection agency or a ion 319).	
Metallic storage tanks for o	oil within mobile food trucks shall be listed under U is.	L 80 or UL 142 and installed in accordance with	
Non-metallic storage tanks	s for oil shall be listed for use, including during max	cimum temperatures of use, and not exceeding 200 gallons.	
Normal and emergency vent	ing shall be provided for cooking oil storage tanks	(Section 319).	
	fittings, that is adequately protected from tamperin	nounted and restrained to prevent movement; (c) have g and damage; (d) have an LP-gas alarm system installed	
Applicant Signature		Date	